



POWERED BY
KOOP

Skid Steer - Diesel

Model : HS10T

Australia-Wide Delivery with Low Freight Costs

Enjoy the convenience of nationwide delivery with our competitive freight rates.

Competitive Financing / Rent-to-Own Options Available

Take advantage of our attractive financing solutions tailored to meet your needs.

HANDYMAX

ABN: 78 643 556 030

2/22 Park Drive

Dandenong South VIC 3175

Phone: **03 9769 2888**

24/7: **1300 077 999**

sales@handymax.com.au

www.handymax.com.au

KEY FEATURES

Reliable KOOP 4-stroke diesel engine with forced air cooling for extended durability.

Versatile 4-in-1 bucket with 2,000 mm dumping height maximizes jobsite efficiency.

Hydraulic system delivers 30 LPM flow at 2,031 psi for smooth, responsive operation.

Low 880 kg operating weight makes it easy to transport and maneuver.

Manual quick hitch system allows fast and tool-free attachment changes on-site.

PRODUCT SPECIFICATIONS

OVERVIEW	
Lift Capacity	200 kg
Quick Hitch Type	Manual Quick Hitch
Drivetrain Type	Rubber Track
Max. Travel Speed	2.5 km/h
ENGINE	
Engine Make	Koop
Engine Model	KD192FC
Displacement	0.499 L
Cooling Type	Forced air-cooled system
Fuel Type	Diesel
Engine Net Weight	50 kg
Engine Power	10hp / 7.6kw @ 3,000 rpm
Engine Type	4-stroke, vertical, single-cylinder diesel engine
Max. Torque	25 N.m @ 2,860 rpm
Rotary Direction of Crankshaft	Clockwise from flywheel end
WEIGHTS	
Operating Weight	880 kg
SERVICE REFILL CAPACITIES	
Engine Oil	15W-40
Engine Oil Capacity	1.65 L
Hydraulic Oil	ISO 46
Air Filter	Part No.4678719
Air Filters Change Interval	100h or 3 months, whichever comes first
Hydraulic Oil Change Interval	every 500 hours or earlier if the oil becomes contaminated
BUCKET	
4in1 Bucket Width	1,000 mm
4in1 Bucket Struck Capacity	0.085 m³
4in1 Bucket Heaped Capacity	0.12 m³
HYDRAULIC SYSTEM	
Hydraulic Flow Rate	30 LPM
Operating Pressure	2,031 psi
DIMENSIONS	
Dumping Height	1,800 mm
Max. Dumping Height (with 4in1 Bucket)	2,000 mm
Overall Length (with 4in1 Bucket)	2,220 mm
Overall Length (without Attachment)	1,750 mm
Overall Width (with 4in1 Bucket)	1,000 mm
Overall Width (without Attachment)	920 mm
Overall Height	1,365 mm
Min. Ground Clearance	115 mm
Departure Angle	21°
Bucket Unloading Angle	30°
Bucket Dumping Angle	30°

OPTIONAL ATTACHMENTS

**4in1 Bucket, Skid Steer, S1**

Quick Hitch Type: Handymax S1 , Outside Width: 1000 mm , Struck Capacity: 0.085 m³ ,
Heaped Capacity: 0.12 m³
SKU: 8067188

\$3,718.00
Incl GST

**Auger, Post Hole Digger, S1**

Drilling Diameter: 300 mm
SKU: 7971812

\$1,969.00
Incl GST

**Auger, Post Hole Digger, S1**

Drilling Diameter: 400 mm
SKU: 7479171

\$2,189.00
Incl GST

**GP Bucket, Skid Steer, S1**

Weight: 58.5 kg , Overall Length: 980 mm
SKU: 7029821

\$990.00
Incl GST

**Pallet Forks, Skid Steer, S1**

SKU: 7027121

\$990.00
Incl GST

**Trencher, S1**

Cutting Width: 100 mm , Max. Cutting Depth: 800 mm , Quick Hitch Type: Handymax S1 ,
Overall Width: 612 mm , Overall Height: 666 mm , Overall Length: 1724 mm
SKU: 7568708

\$3,949.00
Incl GST

ABOUT HANDYMAX



Handymax Machinery is an Australian-owned and operated company dedicated to providing high-quality, cost-effective machinery solutions. Our diverse product range includes versatile wheel loaders, robust forklifts, and efficient excavators, all engineered for maximum efficiency and productivity across various industries.

We pride ourselves on innovation and reliability, ensuring each piece of equipment meets the highest standards. Our commitment to customer satisfaction is evident in our attentive service, extensive inventory, and competitive pricing. With our new, spacious headquarters at 2/22 Park Drive, Dandenong South, VIC 3175, we are better equipped than ever to serve our valued customers.

Trust Handymax Machinery to be your reliable partner for all your equipment needs, and join us in driving Australia's prosperity forward.

DISCLAIMER AND USAGE TERMS

Please note that there may be differences between the actual machine and the images or descriptions provided in this brochure. Handymax is committed to continuous improvement and reserves the right to make changes to the product at any time. This brochure is intended for descriptive purposes only. Specifications, dimensions, and illustrations are subject to change without notice. All performance and capacity specifications are based on engineering data and may vary slightly in actual applications. For the most up-to-date information, please contact our technical support team. Handymax endeavors to ensure all information in this brochure is accurate at the time of publication. However, if you find any inaccuracies or omissions, please contact us at marketing@handymax.com.au. Your feedback helps us improve our documentation and service.

© 2025 HANDYMAX

All information contained within this document is protected by copyright and other intellectual property rights owned by Handymax and its licensors. No part of this material may be replicated, reproduced, or copied, either in its entirety or partially, without obtaining prior written consent from Handymax and its licensors. For further details, please contact us to request additional information.

Brochure Version: HS10T.S1.G1.3. Last Updated: 01 Aug 2025.